

The ProTac series expands into weapon-mounted lights with this 350 lumen light featuring a dedicated fixed-mount for Picatinny rails. It uses either a remote switch with momentary/constant on operation or a standard push-button tail switch, and can run on either a lithium battery or an easy-to-find alkaline battery.



TEN-TAP® Programming: Choice of three operating modes: 1.) high/strobe; 2.) high only; 3.) low/high
CR123A lithium battery output: - High for bright light: 350 lumens; 12,000 candela; 219m beam; runs 1.75 hours - Low for longer run time: 40 lumens; 1,380 candela; 19m beam; runs 14.5 hours
AA alkaline battery output: - High: 150 lumens; 4,950 candela; 141m beam; runs 1.5 hours - Low: 40 lumens; 1,380 candela; 19m beam; runs 8 hours
Strobe for signaling or disorienting
One handed snap-on & tighten interface keeps hands away from muzzle when attaching/detaching

Durable, anodized aluminum construction with impact-resistant tempered glass lens
IPX7 waterproof to 1 meter for 30 minutes (with standard button switch) IPX4 water-resistant (with remote pressure switch)
Operating temperature: -40° F to +120° F
Length: 4.25 in. (10.8 cm) 4.3 oz (121.9 grams) with CR123 battery; 4.5 oz (127.5 grams) with AA alkaline battery
Limited lifetime warranty Visit www.streamlight.com for full warranty information
88058 - ProTac Rail Mount 1 with alkaline and lithium batteries

The ProTac series expands into weapon-mounted lights with this 625 lumen light featuring a dedicated fixed-mount for Picatinny rails. Uses either a remote switch with momentary/constant on operation or a standard push-button tail switch.



<p>TEN-TAP® Programming: Choice of three operating modes: 1.) high/strobe; 2.) high only; 3.) low/high - High for bright light: 625 lumens; 22,000 candela; 297m beam; runs 2 hours - Low for longer run time: 60 lumens; 2,000 candela; 89m beam; runs 21 hours Strobe for signaling or disorienting</p>	<p>IPX7 waterproof to 1 meter for 30 minutes (with standard button switch) IPX4 water-resistant (with remote pressure switch)</p>
<p>One handed snap-on & tighten interface keeps hands away from muzzle when attaching/detaching</p>	<p>Operating temperature: -40° F to +120° F</p>
<p>Durable, anodized aluminum construction with impact-resistant tempered glass lens</p>	<p>Length: 5" (12.7 cm); 5 oz. (141.7g) with batteries</p>
	<p>Limited lifetime warranty Visit www.streamlight.com for full warranty information</p>
	<p>88059 - ProTac Rail Mount 2 with two CR123A lithium batteries</p>